

R6



➔ Standalone Access Control Terminal

LED Indicator: Green, Red

Keypad: White backlit, Numeric keys 0~9,

Function keys *, #, Bell

Verification Type: Card, PW, Card/PW, Card+PW

Built-in Card Reader: EM card

(Optional Mifare card)

Card Capacity: 1010

Password Capacity: 8 Password Groups

Log Capacity: N/A

Communication: N/A

Access Control Interface: Electric lock, Door sensor, Alarm, Exit button and Doorbell

Power In: 12V DC

Operating Temperature: -20°C - 50°C

Operating Humidity: <= 95%

Dimension(W x H x D): 52 x 118 x 24 mm

Ingress Protection Rate: IP65

Features:

- ▶ Reads password and/or 125KHz EM card;
- ▶ Customizable to read 13.56MHz Mifare card
- ▶ Anti-vandal, Waterproof & Back-lit Metal Key Buttons
- ▶ Audible beep and visible indicator provide feedback for the user
- ▶ Access control interfaces for electric lock, door sensor, alarm, exit button and doorbell
- ▶ Lock control delay, Unlock duration, Alarm delay are programmable from 0 to 255 second
- ▶ Tamper alarm, door sensor alarm, error operation alarm
- ▶ Slim, elegant and rugged design