

**F18**



## ➔ Standalone TFT Fingerprint Access Control Reader

Users : 3000 Fingerprints

Transaction Storage : 1,00,000 Logs

Sensor : 500 DPI Optical Sensor

CPU : 32 bit High End Microprocessor

Communication : RS485 , TCP/IP , USB-Host

Wiegand Signal : Input / Output

Identification Speed :  $\leq 2$  sec

FAR :  $\leq 0.0001\%$

FRR :  $\leq 1\%$

Operating Temperature :  $0^{\circ}\text{C} - 45^{\circ}\text{C}$

Operating Humidity : 20% - 80%

Optional Feature : Mifare Card

Power : 12V DC, 400mA

Display : TFT LCD Display

Dimension(LxWxD) : 183 x 80 x 42 mm

Weight : 1.36 Kg

### Features:

- ▶ Three different kinds of interface style , including common, matrix and magic styles
- ▶ Sleek and Compact design for narrow spaces
- ▶ Reliable, durable and highly accurate infrared detection fingerprint sensor
- ▶ Reads fingerprint and/or RFID cards
- ▶ Built-in Serial and Ethernet ports
- ▶ Built-in Wiegand input/output port for connection to third party access control panels
- ▶ Audio-Visual indication for acceptance and rejection of valid / invalid fingers
- ▶ Tamper switch and alarm contacts