

Technical Specifications

RV8030-L3

Key Features

- 1/3" HQIS
- 3.6mm Fixed Lens
- 700 TVL Resolution and High Quality Picture
- AGC, BLC, AES
- IR-cut Filter
- Min. Illumination 0.1 Lux
- DC 12V
- Dual Color Metal Case



Model	RV8030-L3	
Image Sensor	1/3" HQIS	
Scanning	2:1 Bank Scanning	
Sync	2:1 Bank Scanning	
Resolution	700 TVL	
Minimum Illumination	F 1.2, 0.1Lux	
S/N Ratio	> 48dB (AGC off)	
Lens	3.6mm Board Lens (Optional 6mm)	
Electronic Shutter	NTSC: 1/60sec ~ 1/100,000sec	PAL: 1/50sec ~ 1/110,000sec
Iris Mode	AES	
White Balance	3200~10000°K	
Backlight Compensation	Auto	
Auto Gain Control	+18dB	
IR LED	36 x Ø 5mm IR LED	
IR-cut Filter	Yes	
Video Output	Composite 1.0Vp-p (75Ω)	
Power Source	DC 12V ± 10%	
Power Consumption	100mA (IR Off), 320mA (IR On) ± 5%	
Operating Temperature	0°C to 50°C	

Designs and Specifications Subject to change without notice.