

Technical Specifications

RV3230 (Sony Effio)

Key Features

- 1/3" Sony Effio Exview Super HAD II
- 3.6mm Fixed Lens
- 700 TVL Resolution and High Quality Picture
- AGC, BLC, HLC, Electronic Shutter
- Min. Illumination 0.1 Lux
- OSD control via cable
- DC 12V



| Model | RV3230 | |
|------------------------|-------------------------------|-----------------------------|
| Image Sensor | 1/3" Sony Exview Super HAD II | |
| Number of Pixel | NTSC: 1020(H) x 508(V) | PAL: 1020(H) x 508(V) |
| Resolution | 700 TVL | |
| Minimum Illumination | F 1.2, 0.1Lux | |
| S/N Ratio | > 48dB (AGC off) | |
| Lens | 3.6mm Board Lens | |
| Electronic Shutter | NTSC: 1/60sec ~ 1/100,000sec | PAL: 1/50sec ~ 1/110,000sec |
| Iris Mode | AES | |
| White Balance | OSD Control | |
| Backlight Compensation | OSD Control | |
| Gain Control | OSD Control | |
| Day / Night | OSD Control | |
| OSD / 2DNR /WDR | Yes | |
| Video Output | Composite 1.0Vp-p (75Ω) | |
| Power Source | DC 12V ± 10% | |
| Power Consumption | 100mA ± 5% | |
| Operating Temperature | 0°C to 50°C | |

Designs and Specifications Subject to change without notice.