

Technical Specifications

RV-SD10H-IR



Key Features

- PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor
- IR distance up to 50 meters; Multiple languages for OSD menu
- Support ambient light detection
- IR Illumination On 1-15 grade selectable
- Park Action includes Home position, 360° scan/A-B scan/cruise1-3
- Dome ID, baud rate, communication protocol can be changed from OSD
- Supported Protocols : Pelco-D/P
- Plastic housing, indoor

Model	RV-SD10H-IR
Horizontal Rotation Speed	0.1° - 50°/sec
Horizontal Rotation Range	360°
Tilt Rotation Range	94°
Auto Flip	Horizontal 180°, Vertical 90°
Auto Control IR LED	50°/sec
A-B Scan	User Programmable
Dwell Preset	01~64 Level
Preset Points	128
Go To Preset Speed	50°/Sec
Guard Tours	3 Groups
Guard Points	Max 16 Points, Dwell Time User Selectable 02~60 Sec
Park Action	Home Position, 360° Scan / A-B Scan / Guard Tour 1-3
Park Time	1-60 mins
PWR on Action	Memory as Power-off / 360° Scan / A-B Scan / Guard Tour 1-3
Ambient Light Detection	Support
IR illumination On	1-15 Grades Selectable
Communication Protocol	Pelco-D, Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
Operating Temperature	Indoor: 0°~+40°
Operating Humidity	< 95% Non-Condensing
Power	DC12 <3A
IR illumination Distance	Up to 50 meters
Power Consumption	< 20 W
Lightening Protection	Transient Voltage 3000V
Camera Module	Sony
LED Angle of illumination	Ø16°2

Designs and Specifications Subject to change without notice.