



This range of lightweight, corrosion-free and weatherproof horn loudspeakers cover the spectrum of sound required for general sound reinforcement.

These highly effective units give clarity of speech and directional sound reproduction and are supplied complete with a stainless steel bracket. The ABS plastic is unaffected by most chemicals.

The units are available with or without transformer and BS5839, part 8 compliant options.

Features:

- IP66
- up to 125 dB(A)
- 10, 15 and 30W versions
- Corrosion-free abs plastic
- Stainless steel mounting bracket
- BS5839-8 Compliant versions available

Model	MR-10	MR-15	MR-30
Power	10W (100V line)	15W (100V line)	30W (100V line)
Output	115dB(A) @ 10W	119dB(A) @ 15W	125dB(A) @ 30W
Sensitivity	105dB(A) @ 1W	108dB(A) @ 1W	110dB(A) @ 1W
Tappings (100V)	1, 3, 5, 10W (selected by rotary switch)	1, 3, 5, 10, 15W (selected by rotary switch)	1, 3, 5, 10, 15, 30W (selected by rotary switch)
Frequency range	280-12,000Hz (dependant on model)		
Dispersion @ 1kHz	100° - 110° Conical (dependant on model)		
Temperature	20°C to +60°C		
Protection	IP66		
Terminations	500mm Flying lead		
Mounting	Stainless steel "U" Bracket		
Weight	1.1kg - 1.6kg with transformer (dependant on model)		
Construction	ABS		

Model	MR-10	MR-15	MR-30
Material		Aluminium	
BS5839-8		Versions available	
Colour		Light cream	